



Blended Cement Type IL

Manufacturer:

Fairborn Cement Company

3250 Linebaugh Road – Xenia, OH 45385

(800) 762-0400 - www.fairborncement.com

Product Description and Basic Uses:

The Fairborn Cement plant produces a blended portland-limestone cement (PLC) which meets the requirements for Type IL cement. Fairborn PLC is formulated with interground limestone not exceeding 15% by weight.

Type IL

Fairborn portland-limestone cement (PLC) is engineered with a higher limestone content to reduce the carbon footprint of concrete, performs similar to Type I,II cement, and is suitable for the same applications. Fairborn PLC possesses moderate sulfate resistance and moderate heat of hydration properties.

Quality:

Fairborn Cement Company is committed to quality and takes pride in the products we manufacturer. We use only high quality raw materials and strict quality control procedures, and are the local leader in quality cement production.

Standards:

Type IL cement meets the standard requirements of ASTM C595 / AASHTO M240, Standard Specification for Blended Hydraulic Cements.

Availability:

Fairborn Type IL portland-limestone cement is available in bulk and bagged quantities through our plant and terminal network, and can be ordered by contacting Fairborn Sales at (800) 762-0400.

Additional Information:

Additional information can be obtained by visiting:

www.fairborncement.com

Product Precautions:

Products may cause severe burns and injuries to the skin, eyes, lungs and digestive system. Avoid contact with skin and eyes. Wash exposed skin with soap and water. In case of eye contact, flush eyes immediately and thoroughly, and in both instances, consult a physician immediately. Breathing Product dust may cause nose, throat or lung irritation or choking. Prolonged exposure to Products may cause lung injury, including silicosis and products may contain crystalline silica, a substance that may cause lung cancer. If breathing becomes difficult due to exposure, remove exposed person to fresh air and consult a physician. Gross ingestion of products may cause digestive system injuries or intestinal discomfort. If ingestion occurs, do NOT induce vomiting, but drink plenty of water and consult a physician. Keep out of the reach of children. Follow directions and warnings on Product packaging. For other precautions, please refer to the Fairborn Cement Company's Safety Data Sheets for portland cement.

Warranty:

LIMITED WARRANTY. The Products shall conform to applicable specifications of the American Society for Testing and Materials, and such other specifications. Seller, having no control over the use of the Product does not guarantee finished work, nor shall Seller be responsible for the condition of the Product after delivery to the Buyer. Charges incident to inspection or testing made by or on behalf of Buyer to determine compliance with specifications shall be paid for by Buyer.

EXCEPT FOR THE LIMITED WARRANTY MADE ABOVE, SELLER SPECIFICALLY DISCLAIMS ANY OTHER WARRANTY, INCLUDING ANY EXPRESS WARRANTY, ANY IMPLIED WARRANTY OF MERCHANTABILITY OF GOODS, AND ANY IMPLIED WARRANTY OF FITNESS OF GOODS FOR ANY PARTICULAR PURPOSE, ALL OF SUCH WARRANTIES ARE EXCLUDED AND SPECIFICALLY DISCLAIMED BY SELLER.